

























14		BLB-5207	1.CCT:W/CW/WW2700-1300K Color: 	Epistar SMD 5050 w	0.48W	40 lm	1.5
15		BLB-5207-(R/G/B/Y)	2.20 pcs one string 3.Power: 0.48w/pcs 4.Voltage: 12V DC	 EpistarSMD3535	0.48W	/	1.7
16		BLB-5401	5.Luminous: 40lm/pcs 6.Viewing Angle :140°	Epistar SMD 5730	1w	100 lm	2
17		BLB-5401 -s	7.Ingress protection :IP65 8.Size: 49*15.3*6.8	Samsung5630	1w	100 lm	2.4
18		BLB-5208	1.CCT:W/CW/WW2700-1300K Color: 	Epistar SMD 5050	0.72W	60 lm	1.7
19		BLB-5208-(R/G/B/Y)	2.20 pcs one string 3.Voltage: 12V DC	 EpistarSMD5050	0.72W	/	2.4
20		BLB-5402	4.Luminous: 60lm/pcs 5.Viewing Angle :140°	Epistar SMD 5730	1.5w	150 lm	1.9
21		BLB-5402-s	6.Ingress protection :IP65 7.Size: 70*15*7	Samsung5630	1.5w	150 lm	2.7
22		BLB-5501	1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 150lm/pcs 5.Viewing Angle :140° 6.Ingress protection :IP65 7.Size: 85*17*7	Epistar SMD 5730	1.44w	150	2.2
23		BLC-5901	1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 60lm/pcs 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 80*15*5	Epistar SMD 5050	0.72w	60	1.4
24		BLC-5901-(R/G/B/Y)	1.CCT:  2.20 pcs one string 3.Voltage: 12V DC 4.Viewing Angle :120° 5.Ingress protection :IP65 6.Size: 80*15*5	Epistar SMD 5050	0.72w	/	1.6
25		BLC-5902	1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 60lm/pcs 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 70*13*4	Epistar SMD 2835	0.72w	60 lm	1.4
26		BLC-5902-(R/G/B/Y)	1.CCT:  2.20 pcs one string 3.Voltage: 12V DC 4.Viewing Angle :120° 5.Ingress protection :IP65 6.Size: 70*13*4	Epistar SMD 2835	0.72W	/	1.6
27		BLD-5201	1.CCT: W/CW/WW 2. One pcs one group 3. 20 pcs one string 4. Voltage: 12V DC 5. Viewing Angle :120° 6. Ingress protection :IP65 7. Size: 68.2*19.5*5.7	Epistar SMD 5050	0.72w	60 lm	1.3
28		BLD-5201-(R/G/B/Y)	1. Color :  2. One pcs one group 3. 20 pcs one string 4. Voltage: 12V DC 5. Viewing Angle :120° 6. Ingress protection :IP65 7. Size: 68.2*19.5*5.7	Epistar SMD 5050	0.72w	/	1.7

29		BLD-5202	<p>1.CCT: W/CW/WW 2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Luminous: 80lm/pcs 6.Viewing Angle :120° 7.Ingress protection :IP65</p>	Epistar SMD 5050	0.96w	80 lm	1.5
30		BLD-5202-(R/G/B/Y)	<p>1.Color:  2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 54.8*33.2*5.9</p>	Epistar SMD 5050	0.96w	/	1.9
31		BLD-5302	<p>1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 150lm/pcs 5.Viewing Angle :120° 6.Ingress protection :IP65 7..Size: 68.2*19.5*5.7</p>	Epistar SMD 5730	1.5w	150lm	1.5
32		BLD-5301	<p>1.CCT: W/CW/WW 2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Luminous: 200lm/pcs 6.Viewing Angle :120° 7.Ingress protection :IP65</p>	Epistar SMD 5730	2w	200lm	2
33		BLD-5201Q	<p>1.Color:  RGB 2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 68.2*19.5*5.7</p>	 RGB EpistarSMD5050	1.08w	/	2.4
34		BLD-5202Q	<p>1Color:  RGB 2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 54.8*33.2*5.9</p>	 RGB EpistarSMD5050	1.44w	/	2.7
35		BLE-1004	<p>1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 165 lm/pcs 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 75*12</p>	Epistar SMD 5730	1.5w	165 lm	0.45
36		BLE-1204	<p>1.CCT: W/CW/WW 2.20 pcs one string 3.Voltage: 12V DC 4.Luminous: 200lm/pcs 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 36*36*6</p>	Epistar SMD 5730	2w	200 lm	0.8
37		BLE-1205Q	<p>1.Color: RGB 2.One pcs one group 3.20 pcs one string 4.Voltage: 12V DC 5.Viewing Angle :120° 6.Ingress protection :IP65 7.Size: 75*12</p>	Epistar 5050RGB	0.72w	/	0.8
38		BLE-1204Q	<p>1.Color: RGB 2.20 pcs one string 3.Voltage: 12V DC 4.Viewing Angle :120° 5.Ingress protection :IP65 6.Size: 36*36*6</p>	Epistar 5050RGB	1.44w	/	0.89

Item	Images	Specifications	Model	LEDs	Power (W/roll)	Luminous (LM)	RMB
39		1. Luminous: 16lm/pcs(W) 2. LED qty: 60pcs/M 3. PCB: 10mm 4. Length: 5m/roll 5. Voltage : 12V DC 6. Ingress protection : IP65 in Epoxy	BS-102-HRO	Epistar SMD 5050 high brightness	14.4W	/	7.5
			BS-102-HGO				7.5
			BS-102-HBO				7.5
			BS-102-HYO				7.5
			BS-102-HWO				7.5
			BS-102-HWWO				7.5
			BS-102-HRGBO				8.5
40		1. Luminous: 16lm/pcs(W) 2. LED qty: 60pcs/M 3. PCB: 10mm 4. Length: 5m/roll 5. Voltage : 12V DC 6. Ingress protection : IP33	BS-101-HRI	Epistar SMD 5050 high brightness	14.4W	/	6.5
			BS-101-HGI				6.5
			BS-101-HBI				6.5
			BS-101-HYI				6.5
			BS-101-HWI				6.5
			BS-101-HWWI				6.5
			BS-101-HRGBI				7.5
Notes:							
1. Price term: EXW							
3. Payment terms: 50% deposit with PI signed , balance before shipment							
4. Leatime :3- 5 working days after received the deposit if without deposite.							